9321 NE 72th Ave Ste 12, Vancouver, WA 98665

www.ceasefire.com tech@ceasefire.com

1.888.CEASE FIRE (232-7334) | 360.567.0990

CFP 640LP

Low Profile Dry Chemical Suppression System Unit

Interactive 3D graphic. Click to activate and rotate.

Specifications

Maximum Total Flood Volume	8.2'x8.2'x10' = 672.4ft³ / 2.49mx2.49mx3.05m = 18.91m³
Reach Coverage Area	8.20'x8.20' = 64.24ft² / 2.5mx2.5m = 6.25m²
Temperature Rating	-20°F to 120°F / -29°C to 49°C
Cylinder	Worthington
Diameter	7.2" / 18.3cm
Length	11.44"+2.55" Coupling Assembly / 29.06cm+6.48cm
Capacity	7lbs / 3.18kg
Unit Weight	25.25lbs / 11.45kg
Ship Weight	29lbs / 13.15kg
Approvals	UL, ULC, CSFM, NYC #5754
Propellant	High Purity Compressed Dry Nitrogen
Standard System Activation:	155° Fahrenheit / 68.3° Celsius

Safety data sheet


CF-33


Approvals


NYC Fire Dept.
Certificate of Approval
#5754

GACA
الهيئة العامة للطيران المدني
General Authority of Civil Aviation

General Directorate of Civil Defence
Ministry of Interior


11.44
2.55
0.77
8.65
7.2
10.15




11.44
2.55
10